




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06K 9/00		A1	(11) International Publication Number: WO 98/39728
			(43) International Publication Date: 11 September 1998 (11.09.98)
(21) International Application Number: PCT/US98/04011		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 2 March 1998 (02.03.98)			
(30) Priority Data: 08/805,856 3 March 1997 (03.03.97) US 09/032,514 27 February 1998 (27.02.98) US			
(71) Applicant: BACUS RESEARCH LABORATORIES, INC. [US/US]; Suite 8A, 910 Riverside Drive, Elmhurst, IL 60126 (US).			
(72) Inventors: BACUS, James, V.; 4324 Stonewall, Downers Grove, IL 60515 (US). BACUS, James, W.; 20 Natoma Drive, Oakbrook, IL 60521 (US).			
(74) Agents: SAMPLES, Kenneth, H. et al.; Fitch, Even, Tabin & Flannery, Room 900, 135 S. LaSalle, Chicago, IL 60603 (US).			
		Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD AND APPARATUS FOR CREATING A VIRTUAL MICROSCOPE SLIDE



(57) Abstract

A virtual microscope slide is created by using a computer-controlled microscope (10) to capture a plurality of low magnification images of a specimen which are tiled to create a reconstructed macro image (24). A plurality of higher magnification images are also captured and tiled to create a micro image (26). The macro (26) and micro (24) images are then stored, along with their mapping coordinates for later, interactive viewing.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

-1-

**METHOD AND APPARATUS FOR CREATING
A VIRTUAL MICROSCOPE SLIDE**

Field of the Invention

This is a Continuation-In-Part of prior patent
5 application Serial No. 08/805,856, filed March 3, 1997,
which is hereby incorporated by reference in its
entirety. This invention relates to a method of, and an
apparatus for, acquiring and constructing tiled digital
images from a specimen on a support, such as a microscope
10 slide, and for storing, and transferring the image for
viewing by another at a local or remote location.

Background of the Invention

The invention described in the aforesaid
application answers a need, a requirement to image and
15 digitally record an object in a relatively flat plane at
high resolution/magnification. Today, it is impractical
to construct an optical image sensor large enough to
cover the entire image area e.g., of a specimen on a
microscope slide, at the required resolution. This is
20 because lens size and resolution/magnification issues
limit the size of the field of view of magnified objects
and their resulting images. Viewing through a microscope
is akin to viewing through a periscope in that one sees a
very small field of view even at low magnifications, such
25 as 1.25X. A pathologist using a microscope often scans a
slide to obtain in his mind an overall view or sense of
what constitutes the specimen and he remembers the
general locations of the diagnostically significant,
small pieces of the specimen. Usually, these are the
30 diseased areas, such as malignant or potentially
malignant portions of the specimen. To obtain higher
resolution and magnification of these suspicious
portions, the pathologist switches to a higher
magnification objective lens but then the field of view
35 becomes much smaller again. Often, the pathologist

-2-

switches back and forth between the lower magnification, larger field of view objective lens to orient himself relative to the specimen and the high magnification, smaller field of view to obtain the detailed, high resolution view of the suspicious area on the specimen. Thus, the user never receives a magnified, condensed overall view of the specimen or a portion of the specimen but must remember the series of views taken at low magnification. Likewise, at high resolution, high magnification, the user never receives or views a collection of adjacent images but must interrelate these successive images in the user's mind.

A similar problem exists on the Internet or intranet where a pathologist may receive a single field of view magnified image taken from a specimen over the Internet or the intranet on his browser. The pathologist must be provided with explanations to coordinate the high resolution view with the lower resolution view. The number of views available to the pathologist is very limited, and the pathologist is unable to select other views or to scroll to neighboring views at the areas that are most interesting to the pathologist.

In the aforesaid prior application, there is disclosed a method and apparatus whereby a person may construct a low magnification, digitized overall, image view of the entire specimen on a slide or a selected portion of the specimen on a slide, such as the basal layer of a tissue section. The overall, low magnification digitized image allows the user to understand where the user is presently located in his viewing and where the user may want to make the next observation. That is, the low magnification overall view is generally in color and provides to the experienced user a visual overall or thumbnail view of the slide and shows the possible areas of interest for malignancy or other diseases which manifest themselves at certain locations on the specimen image being viewed. This low

- 3 -

magnification overall view enables the user to select thereon the points of interest that the user wants to view at a higher magnification.

The overall view was constructed by taking by a
5 large number of low magnification images of the specimen through a microscopic scanning system and then coherently assembling and coordinating these respective smaller views or images (hereinafter "image tiles") into one coherent, low magnification, macro image from the
10 specimen. Often the digitized macro image is reduced in size by a software system to even a smaller size to be displayed on a local screen or to be transferred over a low bandwidth or a high bandwidth channel to a remote viewing screen.

15 The prior application teaches how to assemble a large number of image tiles, for example, 35 image tiles for the macro image, and then to take a series of other tiles of a higher magnification or magnifications which will also be viewed by the user. To this end, the user
20 is provided with a marker, such as a cursor or the like, to select the defined area of interest, and by a simple command, to cause the selected, higher magnification digitized images to appear on the screen for viewing by the user. The higher magnification images may be one of
25 several magnifications or resolutions such as 10X, 20X and 40X.

As disclosed in the aforesaid application, it is preferred to allow the user, such as a pathologist, to quickly flip back and forth between the high resolution
30 micro image and the low macro resolution image or to provide separate split screens whereby the pathologist is shown an overall macro view and a marker showing where the current higher magnification view is located. Because of the multiple magnifications, the user may
35 change to an intermediate magnification such as would be accomplished by switching between intermediate objective lenses. This provides the pathologist with views which

-4-

correspond to changing back and forth between objective lenses in a microscope, a procedure with which most pathologists are familiar and have been trained.

Additionally, the aforesaid application provides
5 the user with a scrolling feature that allows the user to shift into the viewing screen adjacent, magnified images on the screen so that the pathologist is not limited to only seeing just a full tile view but may see adjacent image material from adjacent, neighboring tile images.

10 In the aforesaid patent application, there is a disclosure of transmitting the low magnification image over a local area network or over the Internet through various servers and computers. The tiled images that were being transmitted were achieved by use of a fully
15 computer controlled microscope which allowed the user to navigate along a specimen area of interest, such as along a basal area or to other suspicious points spread throughout the specimen to acquire tiled images of selected areas so that the entire specimen would not have
20 to be digitized and stored. As disclosed in the preferred embodiment in the aforesaid application, an Internet browser remotely-controlled, automated microscope could be used by a pathologist from a remote location to view the reconstructed macro image tiles;
25 and, with his manipulation of the microscope, using an intranet or Internet browser, could acquire single images at higher magnifications if desired. While several people could see the particular digitized images being transmitted out over the Internet as they were acquired
30 by a particular pathologist and several people could view the stored images, there was still a problem of control at operation of the microscope by each person viewing the digitized images, and a problem with acquiring and transmitting large areas of higher magnification images
35 using the tiling method.

As stated above in greater detail, the current state of archiving the digital images achieved through a

-5-

microscope is often by having photographs or by video tapes. The photographs are difficult to use as is a video tape particularly when the user wants to move rapidly back and forth between various images and to
5 scroll through various adjacent parts of the specimen image. Further, current archival methods lack an overall macro image of the specimen, which allows the user to know exactly where the particular high resolution view is from when it is making an analysis of the high resolution
10 image.

While digitized images can be stored magnetically or otherwise digitized and recorded on various recording mediums, no current archival system allows the user to toggle back and forth between high
15 magnification images and low magnification images or between various images at different magnifications such as that achieved by a pathologist switching microscope objective lenses in real time to get the macro and micro images from the same location on the specimen.
20 Heretofore, the practice of pathology has been relatively limited to the use of microscopes and to the pathologist having to use the microscope to review the particular specimen.

There is a need for a dynamic system whereby one
25 or more or several pathologists, including a consulting pathologist, may view the same area simultaneously and interact with one another either in diagnosis or in analysis. Also, it would be best if the images from the specimen could be stored so that a pathologist could
30 easily examine the images at his leisure using an intranet or Internet browser at a later date merely by accessing the particular web site where the images are located.

It will be appreciated that a host of problems
35 need to be solved to allow Internet or intranet users to view on their respective monitors useful, low resolution, macro images and high resolution, micro images of several

-6-

adjacent, original microscope images. One of the first problems is how to seam together neighboring tile images to form a seamless overall view of these tiles. Heretofore, attempts to seam the tiles used software to
5 combine the pixels at the tile boundaries and have been generally unsuccessful. Another problem is that of mapping of coordinates beginning with the coordinates, usually X and Y coordinates, from and at the microscope stage carrying the slide and then the mapping of
10 coordinates on the scanning screen not only for one magnification but also to coordinate the mapping for the respective multiple resolution images taken typically at 1.25X, 10X and 40X or more. These coordinates must be maintained for a large number of tiled images, e.g., 40
15 tiled images for one macro image. In order for the remote user to view these tile images and to flip back and forth between different resolution, tiled images, the user's computer and monitor not only must receive the addresses and stored parameters for each pixel but must
20 also run them on a generic viewing program.

Another problem with acquiring image tiles and sending them over a low bandwidth Internet channel is that both the storage requirements on the server and the amount of data acquired per slide become high, such as
25 for example, 120 megabytes to one gigabyte. The 120 megabytes is only achieved by not taking image tiles of the entire specimen but only image tiles from the areas selected by the pathologist when tracing at high resolution along basal layers or only at the dispersed,
30 suspicious cancer appearing area in a breast cancer. Even with this selective interaction by a pathologist in constructing the macro and micro digitized images with a vastly reduced amount of image tiles relative to that which would be acquired if the entire specimen were
35 imaged at each of the multiple magnifications, the acquired amount of data is a monstrous problem of transmitting in a reasonable amount of time over a narrow

-7-

bandwidth channel to an ordinary web browser having limited storage capacity. While rough compression techniques could be used, they cannot be used at the expense of providing the high resolution image that the pathologist must have for diagnosis of the specimen.

Summary of the Invention

In accordance with the present invention, there is provided a new and improved method and apparatus for constructing digitally scanned images from a microscope specimen, for storing the digitally scanned images in a tiled format convenient for viewing without a microscope, and for transferring the tiled images at multiple magnifications for viewing by another at a remote location. This is achieved by assembling together several adjacent, original microscope views at a first magnification to obtain an overall macro view of the specimen and assembling together several adjacent original microscope views at a higher magnification to create a combined data structure. The data structure may then be transferred to the remote viewer to provide this viewer multiple resolution macro and micro images of areas on the slide specimen. The data structure is constructed by digitally scanning and storing the low magnification images with their mapping coordinates and likewise, digitally scanning and storing higher magnification images with their mapping coordinates. Further, a pathologist may interactively select only those diagnostically significant areas of the specimen for digital scanning and storing to reduce significantly the number of image pixels stored at high resolution.

The data structure can be transmitted over the Internet or intranet to allow multiple users to consult on a particular microscope each using his own virtual images of the specimen. These users each may flip back and forth between different resolution images in a manner similar to that achieved when shifting among objective

-8-

lens for different resolution views. However, the preferred embodiment of this invention provides a marker on the overall macro view showing the remote user where the higher resolution image is located on the specimen so
5 that the user does not have to remember the location of the higher resolution image. Unlike the single, small optical field of view currently available, the remote user is provided with a series of abutted, tiled images each being substantially equal to one small optical field
10 of view. Thus, the remote user is provided with better and larger macro and micro tiled images than the single, small optical fields of view taken at the same magnifications of a single tiled image.

The preferred data structure is also provided
15 with a generic viewing program that allows the remote user to manipulate and interpret the tiled images on the user's browser. This generic viewing program is self-contained with its own display and the interpretative program is usable with a variety of computers, browsers
20 and monitors. The data structure uses selectively compressed data to reduce the huge amount of acquired data, e.g. 120 megabytes, into a small amount of data, e.g. 1.4 megabytes. Such smaller, more manageable amounts of data can be transmitted over a low bandwidth
25 channel such as the Internet without the loss of resolution that would interfere with the remote pathologist's analysis. Further, the interactive program allows the pathologist to scroll and to view neighboring image areas of neighboring image tiles which were
30 currently unavailable to the pathologist until the inventions set forth in the aforesaid application and in this application.

Turning now in greater detail to aspects of this invention, problems with achieving tileable (i.e.
35 contiguous images which can be seamlessly abutted next to each other to recreate the original image, but at different magnifications) multiple images of a specimen

-9-

on a microscope slide are overcome by the system of the invention. The system includes a microscope and stage in which digital locations on the stage have been predetermined in accordance with an electromechanical addressable coordinate system (X-Y for convenience). Each point on the stage is assigned an "X" and a "Y" coordinate which uniquely defines its location. The increments in each of the X and Y directions are established at a predefined amount for example in .1 micrometer increments. A key factor in achieving superior resolution of the specimen images at higher magnifications is to establish many more physical increments on the stage for each pixel of the image sensor and of the intended display. For example, at 1.25X magnification, 64 points on the stage correspond to one pixel on a CCD optical sensor, which corresponds to one pixel on a 640 by 480 monitor (for a VGA display), using the bitmap addressing and scrollable image method described herein.

Once the coordinate system is defined for the microscope stage, when a specimen on a microscope slide is placed on it, each feature of interest on the slide can be uniquely located with reference to the stage. Then the microscope system is used to digitally scan the image. The first scan is done at a relatively small magnification since this image will be used to provide a "macro" image of the entire specimen. In the preferred embodiment, 1.25X magnification is used. The microscope system then scans the slide using the 1.25X objective. Since the image is detected by rectangular optical sensors, such as the optical sensors in a CCD grid, the stage must be moved in relatively larger increments to place the next adjacent physical part of the slide exactly in the region where that rectangular area will be precisely imaged on the CCD sensor.

Although the area traveled is relatively large, the precision must be high to enable alignment of the

-10-

image parts within the pixel resolution of the CCD sensor. For example, at the 1.25X magnification, 48,143 X steps and 35,800 Y steps are necessary to move the specimen object on the stage to a new, contiguous region for optical imaging on the CCD sensor. The signal produced by the optical sensors in the CCD grid are then transmitted to a computer which stores the image signals in a series of tiled images. Since each image frame is defined by predetermined X-Y coordinates, these can be easily converted into a series of contiguous tiled images.

To view the scanned digital image on a monitor, the computer uses a method of reserving an image bitmap corresponding to the entire size of the tiled image, e.g., in this instance, 10 x 8, 1.25X magnified tiled images are acquired. This requires an image bitmap of 7,520 x 3,840 in size, using a 752 x 480 pixel CCD sensor. Since the X-Y coordinates are known for each image tile, and thus for each pixel in each tile, the bitmap can be used to coordinate and display the stored image tiles to present a fused macro view of the image with one-to-one pixel correspondence of the screen pixels with the image pixels. Typically, the screen pixels are fewer in X-Y size than the macro tiled image, (that is, the entire image cannot be viewed on the monitor without some sort of image compression); and in this case, the macro tiled image is scrolled on the viewable window segment of the screen to maintain the one-to-one correspondence. An advantage of the one-to-one correspondence is that significant image detail is available to the user. Further, since the physical X,Y position on the specimen is known through the stage coordinate relationship to the image pixels, the tiled macro images can be used to locate regions, and move the stage to that region from collection of higher magnification tiled images.

-11-

Since the nature of optics, i.e. lenses, is that they provide a generally circular image with a sharp central region and with fuzziness around the periphery of the image, the microscope system is designed to step
5 through the various locations on the slide in such a manner to scan only the high resolution image portion in the center of the optical image. The fuzzy outer regions are discarded. This also has the benefit of ensuring a high resolution image once the tiled images are
10 reconstructed for viewing by a user on a monitor.

After the macro image is completed, a trained professional, such as an examining pathologist, views the image of the specimen by viewing the macro image and looking for areas of interest. In general, most specimen
15 slides contain only a few small areas of diagnostic significance. The balance of the slide is generally empty or not significant. When the examining pathologist views the slide, some areas may have been previously marked in the regions of interest for viewing and
20 analysis at higher magnifications. Once these regions are marked, the microscope is set to the desired higher magnification and then only the marked regions are scanned and stored. Alternatively, he may define new areas directly on the macro image. In either case, the
25 regions are outlined using a pointing device, such as a mouse, directly on the viewing window displaying the macro image. As described above with respect to the 1.25X images, since the stage has a predefined coordinate system, the scanned higher magnification image portions
30 can be easily located with respect to the macro image, creating a series of micro images.

The fact that a typical microscope specimen slide contains only limited information of interest and the ability of the system embodying the invention to
35 accurately locate such regions enables the system to create a virtual microscope slide, i.e. a data structure which can be used in place of the actual specimen slides.

-12-

This advantageously enables multiple users to consult on a particular specimen. Additionally, because of the reduced size of the data structures, they can be viewed locally on a personal computer, transmitted over an intranet or via the Internet globally. The created data structures can be stored on a variety of storage or recording media: for example, on a server's hard disk, a Jazz drive, a CD-Rom or the like. Storing the data structure on a portable storage media further enables the transfer and archiving of the microscopic slide data structures by multiple users.

Another feature of the invention is a self-executing data structure. This is achieved by packaging the tiled images with an active, dynamic control program. When an active dynamic control program is used by a viewing program such as a common web browser, the browser can interpret the dynamic control program. This allows the user to interact and control the viewed images seen on the viewer's screen from the recording medium. More specifically, in the preferred embodiment of the invention, a large number of low magnification, digitized tiled images are formed and embedded in a data structure with linking information allowing them to be coherently tiled to each other during viewing to form a macro image, and a series of higher magnification tiled images also similarly constructed into a micro image, and a control program such as a JAVA applet, is provided and transferred with the macro and micro tiled images for use by a remote user. Thus, for example, the macro and micro tiled images with their active control program may be transmitted over an Internet or an intranet to a browser, or other application program for viewing the images, where the user may then access the browser to analyze the images at multiple resolutions and with a macro field of view before the user. This enables the viewing of the images in a manner similar to the use of an optical

-13-

microscope, but in this case visually the view is of a virtual microscope slide at multiple resolutions.

Also, in accordance with the invention, the constructed, tiled macro and tiled micro images along
5 with the control program can be placed on a web server and can be accessed locally and over a wide area, even globally, by multiple users at various times. For instance, a large number of previously scanned and recorded specimen slides, such as 300 specimen slides,
10 may have their respective micro and macro tiled images put on a server. Medical students or pathology students then may each access the slide or all of the 300 slides and review them on their respective web browsers at their leisure. Likewise, a pathologist may dial up or
15 otherwise connect through an internet service provider to the Internet or other long-level network and access a web server and obtain a particular patient's specimen results. Those results would have been stored as a data structure (including macro and micro tiled images along
20 with the control and interpretative program). The pathologist then may and perform an analysis at his home or in his office without needing to have or to control a microscope or the particular slide. The pathologist may toggle back and forth between the micro and macro images,
25 and then dictate or otherwise prepare his analysis, findings or diagnosis from these stored images. This advantageously enables the pathologist to perform part of his job in the convenience of his home or office and also enables a laboratory to maintain actual specimen slides
30 in a safe and secure location, away from the potential of damage and without the necessity of shipping the slides for microscopic examination at a remote location.

The control program, which in the preferred embodiment of the invention is a dynamic self-executing
35 program such as a JAVA applet, allows the user to manipulate and interpret the images while on a browser. The dynamic, self-executing program is completely self-

-14-

contained with its own display and interpretative program for operation by the user of the browser.

The present invention is not limited to use on a browser since the tiled, digitized images and the active, control program may be stored on a CD-ROM or other portable storage medium and sent through the mail, or otherwise transferred to the user for review at the user's convenience with dedicated viewers.

Thus, from the foregoing, it will be seen that there is provided a new and improved method of and apparatus for archiving of microscopic slide information on a storage medium with an active control program, which allows the display and interpretation of various micro and macro images.

In accordance with another important aspect of the invention, there is provided with the self-executing data structure (the stored macro images, micro images and dynamic, self-executing program for viewing, reconstructing and manipulating the stored images) the ability to scroll through the displayed images. This allows the user not only to see one image tile at a particular magnification, but also to use a pointer or to otherwise move a point to cause displayed images from adjacent neighboring image tiles which were not previously viewable to be included in the field being viewed by the user. That is, the user may shift the viewing location across tile boundaries from one tile to another, and up or down, or right or left or to other points of interest in a normal two-dimensional scrolling manner. Thus, the user is provided with an archived stored slide at multiple magnifications which can be readily scrolled through in any arbitrarily chosen direction or directions. As in the aforesaid application, the user interactively will go to various areas of selected interest and operate a pointer or a marker to select for high magnification viewing the

-15-

particular area of interest and also do a scrolling of neighboring areas of interest.

In addition to the Internet browser, the data images can be viewed, reconstructed and manipulated using a dynamic, self-executing program such as, for example, a JAVA applet or an ACTIVE-X applet. An advantage of using a dynamic, self-executing program which is linked with the data images on a data structure is that the data images can be viewed, reconstructed and manipulated independent of the operating system of the users computer. Additionally, the user does not have to acquire the latest version of the dynamic, self-executing program since it is already linked with and provided with the data images on the data structure or on the storage medium. Thus, the user can always view the data images, regardless of different program versions.

The dynamic, self-executing program permits interchanging the image in its entirety simulating the visual effect of changing objectives in a regular, mechanical optical microscope view. Thus, the user can easily switch from one magnification to another and scroll through portions of the image, simulating tracking the image by moving the slide under the microscope lens.

The dynamic, self-executing program permits scrolling the image in a window to enable viewing of the reconstructed large field of view images. The user can use a mouse, or other pointing device, to select a portion of the image on the large field of view image and the program will display that selected portion in another window at the desired magnification.

A method of constructing a record of the digital image of a specimen on a microscope slide using image tiles includes scanning the image at a first low magnification so that substantially all of the specimen is obtained. Then the specimen is scanned at a second higher magnification so that images of selected (or all) sub-portions of the specimen are obtained. The spatial

-16-

relationships of the first lower magnification image to the second higher magnification images is used to reconstruct the image during viewing. The individual, sub-portions or tiles of the scanned image are seamed
5 together by the dynamic, self-executing program to create a digital image of substantially larger areas than individually acquired image fields of view without tiling.

A data structure according to the invention is
10 created by first digitally scanning the desired specimen at a plurality of image magnifications. The scanned images are then stored in a series of contiguous image tiles. Then the stored images are linked with a dynamic, self-executing program. The data structure can be
15 created using a software program. Images are preferably first stored as bitmap files (.bmp). (Note that storing the resulting image files in the bitmap format is different from the bit mapping method of creating the image files described herein.) An image compression
20 program is used to convert the bitmap files to a JPEG (.jpg) format, which requires less storage space and consequently less time to display on a computer. The person creating the data structure can select how much detail to include in the conversion. JPEG images can be
25 created for example, using 20 to 80% compression ratios of the original image. An advantage of the JPEG format is that essentially empty tiles (tiles with mostly white or black space) compress down to very small files. Detailed files, however, do not compress as much.
30 Additionally, the dynamic, self-executing program may include compression algorithms for displaying the entire image or portions thereof in the viewing window.

After downloading or installation of a data structure on a storage medium, when the user desires to
35 view the data images, he uses a mouse and "clicks" on the icon for the self-executing data structure. The dynamic, self-executing program displays the image in a window.

-17-

Typically, the program will display a macro or thumbnail view of the entire specimen image at a lower magnification and a smaller window containing a particular image tile or groups of tiles at a higher magnification. The program enables the user to use the mouse or other pointing device to select a point or outline a region on the thumbnail view. The selected view will then be displayed in the smaller window at the second magnification. The user can move the mouse or pointing device and the image in the smaller window will scroll with the selection on the thumbnail view. In this way, the program simulates movement of a microscope slide under the field of view of the mechanical microscope. However, it should be noted that because of the one-to-one correspondence between the CCD pixels and the screen pixels, not all macro images may be able to be displayed on the monitor. The user may scroll through the macro image or select a compression feature to display the entire macro image in the window.

Another feature of the self-executing data structure is that when the image is displayed on the viewing screen, the user can select an image tile or sub-portion of the image and alternately view that portion of the image at each scanned magnification. For example, if the data was scanned at magnifications of 1.25X, 20X and 40X, the user can "click" and see the same tile at each of those magnifications alternately.

Brief Description of the Drawings

FIG. 1 is a block diagram of a system according to the invention for creating and transmitting locally, over an intranet or via the Internet data structures of an image of specimen on a microscope slide;

FIG. 1A is representation of a microscope slide which has been arbitrarily assigned to be scanned into eighty tiled images;

-18-

FIG 1B is a representation of the detected signals of the individual pixel sensors in a CCD optical array after detecting a selected image area to tile and the referenced data files containing the information
5 describing the detected signals;

FIG. 2 is a screen view of a system embodying the present invention showing a low magnification image of a specimen on a microscope slide in one window, a high magnification image of a portion of the low magnification
10 image selected by a region marker and a control window;

FIG. 3 is a view of a display screen of the apparatus embodying the present invention showing the control window a low magnification window having a plurality of high magnification micro image regions
15 delineated therein and a high magnification window including one or more of the micro image regions;

FIG. 4 is a view of a macro image of an actual breast cancer specimen displayed at 1.25X as seen on a computer monitor;

20 FIG. 5 is a view of the grid portion of FIG. 4 outlining a region of interest selected by a pathologist displayed at 40X magnification;

FIG. 6 is a block diagram of the steps in the mapping of the scanned image from the optical sensor
25 array to computer bit map in memory to the display on a user's monitor;

FIG. 7A is a file listing such as would be seen under Windows 95 file manager showing the data files included in a data structure for a breast cancer
30 specimen;

FIG. 7B is a file listing of a Java applet for controlling a data structure;

FIG. 8 is file listing such as would be seen under Windows 95 file manager showing the data files
35 included in an alternate data structure for a breast cancer specimen;

-19-

FIGS. 9A and 9B are a block diagram of the apparatus embodying the present invention;

FIG. 10 is a block diagram of a portion of the apparatus shown in FIG. 9 showing details of a mechanical
5 arrangement of a microscope;

FIG. 11 is a flow diagram related to operation of the apparatus;

FIG. 12 is a flow diagram of details of one of the steps in FIG. 11;

10 FIG. 13 is a display screen showing control parameters to be manipulated thereon;

FIG. 14 is a flow chart for a region outlying routine;

15 FIG. 15 is a flow chart for a scanning and analyzing routine;

FIG. 16 is a schematic showing of the limits of travel of the microscope stage with respect to the image tiles;

20 FIG. 16A is a perspective view of the microscope stage and stepper motors and encoders providing a closed loop drive for the motors;

FIG. 17 is a block diagram of a networked system allowing multiple workstations to obtain access to the microscope and to manipulate the microscope locally at
25 each workstation;

FIG. 17A is a view of the system described in connection with FIG. 10; and

FIG. 18 is a block diagram of a remote networked system for distributing and accessing diagnostic images
30 and data, i.e. virtual microscope slides, through a hypertext transport protocol based server directly or over a packet network.

Detailed Description of the Preferred Embodiment

35 FIG. 1 is a block diagram of a system according to the invention for creating, and transmitting over an intranet or via the Internet a virtual microscope slide,

-20-

i.e. interrelated data structures and display procedures depicting at multiple resolutions, images of a specimen on a microscope slide. The system includes a microscope with a digital platform for supporting the microscope slide. Digital platform or stage 11 has been specially calibrated to include a large number of increments for locating portions of specimen images with high precision. After calibration and initial registration of stage 11 in the microscope setup, a microscope slide or other substrate with a specimen to be scanned is placed on stage 11.

For exemplary purposes, the creation of virtual microscope slide specimen according to the invention will be described with respect to a breast cancer specimen. The first step in creating a data structure according to the invention is to establish a macro image of the entire specimen (or that portion of the specimen desired to be stored as the macro image). The purpose for creating the macro or large area thumbnail image is to enable the viewer to see the entire specimen at once and to use the entire image to choose those significant portions thereon for viewing at greater magnification. In this example, the user has selected 1.25X as the magnification to display the entire breast cancer slide. Once specimen 13a has been placed on stage 11, rotating optical assembly 15 are rotated to select lens 17 which corresponds to the 1.25X magnification.

In accordance with the teachings of the prior patent application, the computer controlled microscope is moved to scan the entire image of specimen 13a. The focusing system is programmed to step through increments which detect/select only the high resolution center area of the field of view in order to avoid storing the fuzzy areas at the periphery of the field of view. In this example, the macro image will be stored in a 10 by 8 array, for a total of 80 contiguous image tiles, as shown in FIG. 1A.

-21-

A typical microscope slide is about 77mm by 25mm, where the usable area, without including the label, is about 57mm by 25m. Each of the 80 image segments is about 4.8mm by 3.5mm in dimension. This means each of
5 the 80 image segments will be scanned separately and stored as a separate image tile.

The precision of the microscope systems is set up so that each step of the motor has a precision of .1 micron (micrometer). In this example, the microscope is
10 set up to move 48,143 steps in the X direction and 35,800 steps in the Y direction at 1.25X magnification for each of the 80 image areas. At higher magnifications, the image areas to scan are considerably smaller, so the number of steps is corresponding smaller. For each of
15 the 80 image areas, the microscope lens will detect only the high resolution center area of the field of view.

The optical image of the desired image area is then detected by optical array sensor 19 (preferably a CCD sensor array). In this example, each of the 80
20 scanned areas is sensed by the entire array, which includes 752 pixels by 480 pixels. The optical array sensor sends electrical signals indicative of the detected image to microscope controlled computer 32. Computer 32 stores the scanned images, including the top
25 left X-Y stage coordinates for each of the 80 individual areas of the microscope slide. Each of the 80 scanned image areas' pixel locations are stored in a bit mapped file (i.e., a file which contains a map of the location of each bit in the area) which corresponds to the layout
30 of the individual images thereon. Thus, all of the pixels from the image tile derived from region A on FIG. 1A, which is the seventh from the left and in the top row, are individually assigned unique locations in the computer memory's bit-mapped file (FIG. 6), and are also
35 stored in the data structure image tile file as shown in FIG. 1B.

-22-

Each of the stored data image tiles is a standard image file with extension.bmp, and is of the order of one megabyte, i.e. each of the 752 x 480 pixels is stored as 3 bytes of red, green and blue image data
5 (752 x 480 x 32 = 1,082,880 bytes). Since the location of each image tile is known according to the bitmap, the complete microscope image can be recreated by painting (displaying) each image tile in accordance with its grid location. It should be noted

10 To display the resulting image, computer 32 calculates the appropriate portion to be displayed from each image tile depending upon the relative size of the display screen. Since the stored image data is usually greater than the size of the typical monitor, the viewer
15 must scroll through the image on the window to view it entirely. However, an optional compression algorithm can be used to compress the entire image into the viewing window. The X-Y coordinate information is used by the viewing and manipulation program to reconstruct the image
20 tiles into a complete image of the specimen. The resulting image is larger, and with better resolution than would be achieved if optics technology were able to construct a single lens capable of viewing the entire specimen in one field of view. In this example, each of
25 the 80 image tiles has digital resolution of 752 x 480 pixels, with corresponding optical resolution of approximate .2 microns at 40X to approximately 6.4 microns at 1.25X.

After the macro or thumbnail images are
30 digitally scanned and stored with their X-Y coordinate information, the user then examines the macro image or original specimen for significant details. Typically, the user will highlight with a marking pen the areas to be viewed at higher magnification. The user then changes
35 the magnification of optics system 15 to the desired higher magnification, moves the scanning system to bring the selected region into view. Computer 32 then repeats

-23-

the scanning and image tile creation process for the selected region, but at higher magnification and with a new grid system to locate the scanned selected regions.

In the example, the user has selected region B shown on FIG. 1A to perform a second view at a higher magnification. The user selects, for example, a 40X magnification. The computer calculates the number of tiles to cover the selected area at 40X magnification and sets up a second grid.

It should be noted that region B crosses over several of the larger tiles in FIG. 1A. Because of the extreme precision of the instrument, 0.1 micron resolution, locating such selected regions with high resolution is readily accomplished. As noted above, the compute calculates the size of the image portion, in this case as an example, X = 1500 and Y = 1200 stepping increments. Each image portion at the 40X resolution is detected by the optical sensor array, 752 by 480 pixels. Each resulting data file is stored in a separate, high magnification mapped area of memory so that the computer can easily recall the location of region B, or any of its 200 individual image tiles, when requested by a user.

Once the user has completed selecting and having the computer controlled microscope system scan and store the digital images in image tiles, computer 32 stores the mapped .bmp files along with their coordinate information and creates slide image data structure 31 in FIG. 1. Slide image data structure includes all of the bitmap image tile files at both magnifications (note that similarly, additional images could be stored at further magnifications, if desired), as well as X-Y coordinate information for the location of the various image tiles.

FIG. 7A is a file listing such as would be seen under a Windows 95 file manager showing the data files included in a data structure for a breast cancer specimen. Included in the file listing are FinalScan.ini and SlideScan.ini as well as sixty bitmap data files.

-24-

Slidescan.ini is a listing of all the original bitmap (.bmp) files. The bitmap files represent the individual image tiles in the scan at, say, 1.25X magnifications. Slidescan.ini is set forth below in Table 1 and describes

5 the X-Y coordinates for each image tile file. When the data structure is viewed by a control program, the program uses the X-Y coordinates to display all the image tiles contiguously.

-25-

TABLE 1 -- Slidescan.ini

	[Header]	[Ss17]
	x=278000	x=133571
	y=142500	y=35100
5	lXStepSize=48143	[Ss18]
	lYStepSize=35800	x=181714
	iScannedCount=37	y=35100
	[Ss1]	[Ss19]
	x=181714	x=229857
10	y=142500	y=35100
	[Ss2]	[Ss20]
	x=133571	x=278000
	y=142500	y=-700
	[Ss3]	[Ss21]
15	x=37285	x=229857
	y=106700	y=-700
	[Ss4]	[Ss22]
	x=85428	x=181714
	y=106700	y=-700
20	[Ss5]	[Ss23]
	x=133571	x=133571
	y=106700	y=-700
	[Ss6]	[Ss24]
	x=181714	x=85428
25	y=106700	y=-700
	[Ss7]	[Ss25]
	x=229857	x=37285
	y=106700	y=-700
	[Ss8]	[Ss26]
30	x=229857	x=-10858
	y=70900	y=-700
	[Ss9]	[Ss27]
	x=181714	x=-10858
	y=70900	y=-36500
35	[Ss10]	[Ss28]
	x=133571	x=37285
	y=70900	y=-36500
	[Ss11]	[Ss29]
	x=85428	x=85428
40	y=70900	y=-36500
	[Ss12]	
	x=37285	
	y=70900	
	[Ss13]	
45	x=-10858	
	y=70900	
	[Ss14]	
	x=-10858	
	y=35100	
50	[Ss15]	
	x=37285	
	y=35100	
	[Ss16]	
	x=85428	
55	y=35100	

-26-

```

    [Ss30]
    x=133571
    y=-36500
    [Ss31]
5   x=181714
    y=-36500
    [Ss32]
    x=229857
    y=-36500
10  [Ss33]
    x=278000
    y=-36500
    [Ss34]
    x=278000
15  y=-72300
    [Ss35]
    x=229857
    y=-72300
    [Ss36]
20  x=181714
    y=-72300
    [Ss37]
    x=133571
    y=-72300

```

25 Table 2 is a listing of the file FinalScan.ini, which is a listing the X-Y coordinates of the high magnification image tiles scanned and stored.

TABLE 2 - FinalScan.ini

```

    [Header]
    tPatientID=mda027
    tAccession=
    tOperatorID=jwb
    tTimeOfScan=8/4/97 1:19:56
    PM
35  lXStageRef=278000
    lYStageRef=142500
    iImageWidth=752
    iImageHeight=480
    lXStepSize=1590
40  lYStepSize=1190
    lXOffset=-1900
    lYOffset=-400
    dMagnification=40
    lAnalysisImageCount=105
45  lCalibrationImageCount=0
    [Da0]
    x=214532
    y=65584
    [Da1]
50  x=212996
    y=64400
    [Da2]
    x=211460
    y=65584
    [Da3]
    x=209924
    y=65584
    [Da4]
    x=208388
    y=65584
    [Da5]
    x=206852
    y=65584
    [Da6]
    x=205316
    y=65584
    [Da7]
    x=203780
    y=65584
    [Da8]
    x=214532
    y=64400

```

-27-

	[Da9]	x=209924
	x=212996	y=62032
	y=64400	[Da28]
	[Da10]	x=208388
5	x=211460	y=62032
	y=64400	[Da29]
	[Da11]	x=206852
	x=209924	y=62032
	y=64400	[Da30]
10	[Da12]	x=205316
	x=208388	y=62032
	y=64400	[Da31]
	[Da13]	x=203780
	x=206852	y=62032
15	y=64400	[Da32]
	[Da14]	x=214532
	x=205316	y=60848
	y=64400	[Da33]
	[Da15]	x=212996
20	x=203780	y=60848
	y=64400	[Da34]
	[Da16]	x=211460
	x=214532	y=60848
	y=63216	[Da35]
25	[Da17]	x=209924
	x=212996	y=60848
	y=63216	[Da36]
	[Da18]	x=208388
	x=211460	y=60848
30	y=63216	[Da37]
	[Da19]	x=206852
	x=209924	y=60848
	y=63216	[Da38]
	[Da20]	x=205316
35	x=208388	y=60848
	y=63216	[Da39]
	[Da21]	x=203780
	x=206852	y=60848
	y=63216	[Da40]
40	[Da22]	x=214532
	x=205316	y=59664
	y=63216	[Da41]
	[Da23]	x=212996
	x=203780	y=59664
45	y=63216	[Da42]
	[Da24]	x=211460
	x=214532	y=59664
	y=62032	[Da43]
	[Da25]	x=209924
50	x=212996	y=59664
	y=62032	[Da44]
	[Da26]	x=208388
	x=211460	y=59664
	y=62032	[Da45]
55	[Da27]	x=206852

- 28 -

	y=59664	[Da64]
	[Da46]	x=179204
	x=205316	y=80976
	y=59664	[Da65]
5	[Da47]	x=177668
	x=203780	y=80976
	y=59664	[Da66]
	[Da48]	x=176132
	x=214532	y=80976
10	y=58480	[Da67]
	[Da49]	x=174596
	x=212996	y=80976
	y=58480	[Da68]
	[Da50]	x=173060
15	x=211460	y=80976
	y=58480	[Da69]
	[Da51]	x=171524
	x=209924	y=80976
	y=58480	[Da70]
20	[Da52]	x=180740
	x=208388	y=79792
	y=58480	[Da71]
	[Da53]	x=179204
	x=206852	y=79792
25	y=58480	[Da72]
	[Da54]	x=177668
	x=205316	y=79792
	y=58480	[Da73]
	[Da55]	x=176132
30	x=203780	y=79792
	y=58480	[Da74]
	[Da56]	x=174596
	x=180740	y=79792
	y=82160	[Da75]
35	[Da57]	x=173060
	x=179204	y=79792
	y=82160	[Da76]
	[Da58]	x=171524
	x=177668	y=79792
40	y=82160	[Da77]
	[Da59]	x=180740
	x=176132	y=78608
	y=82160	[Da78]
	[Da60]	x=179204
45	x=174596	y=78608
	y=82160	[Da79]
	[Da61]	x=177668
	x=173060	y=78608
	y=82160	[Da80]
50	[Da62]	x=176132
	x=171524	y=78608
	y=82160	[Da81]
	[Da63]	x=174596
	x=180740	y=78608
55	y=80976	[Da82]

-29-

	x=173060	y=75056
	y=78608	[Da101]
	[Da83]	x=176132
	x=171524	y=75056
5	y=78608	[Da102]
	[Da84]	x=174596
	x=180740	y=75056
	y=77424	[Da103]
	[Da85]	x=173060
10	x=179204	y=75056
	y=77424	[Da104]
	[Da86]	x=171524
	x=177668	y=75056
	y=77424	
15	[Da87]	
	x=176132	
	y=77424	
	[Da88]	
	x=174596	
20	y=77424	
	[Da89]	
	x=173060	
	y=77424	
	[Da90]	
25	x=171524	
	y=77424	
	[Da91]	
	x=180740	
	y=76240	
30	[Da92]	
	x=179204	
	y=76240	
	[Da93]	
	x=177668	
35	y=76240	
	[Da94]	
	x=176132	
	y=76240	
	[Da95]	
40	x=174596	
	y=76240	
	[Da96]	
	x=173060	
	y=76240	
45	[Da97]	
	x=171524	
	y=76240	
	[Da98]	
	x=180740	
50	y=75056	
	[Da99]	
	x=179204	
	y=75056	
	[Da100]	
55	x=177668	

-30-

Computer 32 can also use the scanned image files to create a self-executing data structure. By compressing the .bmp images to .jpg and adding a dynamic, self-executing program which enables the user to view, reconstruct and manipulate the image tiles, the user can use the data structure as a virtual microscope slide of the original specimen. Preferably, the dynamic, self-executing program is a Java applet, such as shown on FIG. 7B.

Computer 32 can provide the slide image data structure 31 directly or via an intranet browser 33 to local viewer 34, or via an Internet server 38. Slide image data structure 37 is shown as being directly accessible from Internet server 38. Alternatively, a user can download the slide image data structure on his own computer 39, use an internet browser 43 and view the reconstructed images. Another alternative is for computer 32 to store the slide image data structure on a CD-rom, Jazz drive or other storage medium.

To view slide image data structure 31 or 37, the user, who for example, has acquired the data structure via a CD-rom, first installs the CD-rom in the CD-rom drive of his computer. Then the user opens up a browser or other applications program which can read the Java applet installed on the CD-rom with the image tiles. Note that in some instances no separate browser program may be required. In some case, the CD-rom may include the complete applications program for viewing, reconstructing and manipulating the image tiles. In the instant example, the user will then select the icon or file listing for the slide image data structure and the control program will display the data files.

FIG. 2 is a screen view of a system embodying the present invention showing a low magnification image 24 of a specimen on a microscope slide in one window, a high magnification image 26 of a portion of the low magnification image selected by a region marker 30 and a

-31-

control window 28. FIG. 3 is a view of a display screen of the apparatus embodying the present invention showing the control window 28, a low magnification window 24 having a plurality of high magnification micro image regions 310 delineated therein and a high magnification window 26 including one or more of the micro image regions 310, 314, 316. FIG. 4 is a view of a macro image of an actual breast cancer specimen displayed at 1.25X as seen on a computer monitor. FIG. 5 is a view of the grid portion of FIG. 4 outlining a region of interest selected by a pathologist displayed at 40X magnification.

Recall that region A in FIG. 1A was about 4.8mm by 3.5mm. This area creates 752 by 480 pixels of sensed data, or 360,930 pixels of information. Each pixel sends information about its location and the image it sensed to the computer. The computer stores this information in a series of data files (typically .bmp format, but .tif or .gif could also be used). Thus, it can be seen that several more pixels of sensed data are available for viewing on a computer monitor operating at 640 by 480. To view the entire image, the user must scroll through the image tiles. However, scrolling need not be done on a tile, by tile basis. Rather, the user scrolls by pointing to a pixel on the monitor.

Figure 6 is a block diagram showing how the control program locates and scrolls through the stored image tiles. Using the example from Figure 1a, a complete data structure has been created. When the user loads the data structure (of the microscope slide) into his personal computer or views it from an Internet browser, the control program recreates a bit map of the stored data. The bit map of the entire slide is shown in Figure 6. Image tile A is also high-lighted. This bit map enables a user to point to or otherwise reference a location on the slide.

The X-Y coordinate information specified in the data structure enables X-Y translation of the specific

-32-

image tiles and specific pixels within the image tile. When the control program first loads the image, because this image file is so large, only a small number of the available tiles are displayed in the active window on the user's monitor. The user uses his mouse or pointing device to scroll through the active window to view the entire macro image. The X-Y coordinate information selected by the mouse translates into specific image tiles or portions therein. The computer takes the mouse pointer information and retrieves the image data from the series of stored tile images and displays them on the monitor for viewing the by user.

Because of the large amount of CCD pixel information stored, actual CCD pixel information can be recreated in the viewing window. The entire system operates in a loop, where the user inputs a mouse location, the computer translates the mouse location from the screen coordinates (screen pixels) to the X-Y coordinates on the bit map.

Similarly, the user may select the high magnification data images. These are outlined by a dark grid, indicating the areas stored. The user operates the mouse in the same manner as described above. The control program locates the stored X-Y coordinates and retrieves the selected parts of the image, CCD stored pixel by CCD stored pixel.

As mentioned above, to save storage space, computer 32 can perform a data compression on each of the image tile files. A preferred data compression is JPEG, which is readily transferred and recognized by most Internet browser programs. Also, JPEG allows flexibility in the amount of data to be compressed, from 20 to 80 percent. FIG. 8 is file listing such as would be seen under Windows 95 file manager showing the data files included in an alternate data structure, one in which the data files have been compressed or converted to JPEG (.jpg) format for a breast cancer specimen. The file

-33-

index.html (shown in Table 3) is the listing which contains the X-Y coordinate information for these data files. This is the information that is read by the dynamic, self-executing program for viewing,
5 reconstructing and manipulating the image tiles into the macro and micro views.

-34-

TABLE 3 -- index.html

```

<HTML>
<TITLE>
DCIS_027 - Web Slide
5  </TITLE>
    <BODY>
    <APPLET CODE=WebSlide/BliWebSlide.class NAME=DCIS_027
    WIDTH=3384 HEIGHT=960 HSPACE=0 VSPACE=0 ALIGN=Middle>
    <PARAM NAME = "tPatientID" VALUE = "mda027">
10  <PARAM NAME = "tAccession" VALUE = ">
    <PARAM NAME = "tOperatorID" VALUE = "jwb">
    <PARAM NAME = "tTimeOfScan" VALUE = "8/4/97 1:19:56 PM">
    <PARAM NAME = "lXStageRef" VALUE = "278000">
    <PARAM NAME = "lYStageRef" VALUE = "142500">
15  <PARAM NAME = "iImageWidth" VALUE = "752">
    <PARAM NAME = "iImageHeight" VALUE = "480">
    <PARAM NAME = "lXStepSize" VALUE = "1590">
    <PARAM NAME = "lYStepSize" VALUE = "1190">
    <PARAM NAME = "lXOffset" VALUE = "-1900">
20  <PARAM NAME = "lYOffset" VALUE = "-400">
    <PARAM NAME = "dMagnification" VALUE = "40">
    <PARAM NAME = "iImageCount" VALUE = "105">
    <PARAM NAME = "lXsStepSize" VALUE = "48143">
    <PARAM NAME = "lYsStepSize" VALUE = "35800">
25  <PARAM NAME = "iScannedCount" VALUE = "37">
    <PARAM NAME = "lStartX" VALUE = "278000">
    <PARAM NAME = "lStartY" VALUE = "142500">
    <PARAM NAME = "Ss1_X" VALUE = "181714">
    <PARAM NAME = "Ss1_Y" VALUE = "142500">
30  <PARAM NAME = "Ss2_X" VALUE = "133571">
    <PARAM NAME = "Ss2_Y" VALUE = "142500">
    <PARAM NAME = "Ss3_X" VALUE = "37285">
    <PARAM NAME = "Ss3_Y" VALUE = "106700">
    <PARAM NAME = "Ss4_X" VALUE = "85428">
35  <PARAM NAME = "Ss4_Y" VALUE = "106700">
    <PARAM NAME = "Ss5_X" VALUE = "133571">
    <PARAM NAME = "Ss5_Y" VALUE = "106700">
    <PARAM NAME = "Ss6_X" VALUE = "181714">
    <PARAM NAME = "Ss6_Y" VALUE = "106700">
40  <PARAM NAME = "Ss7_X" VALUE = "229857">
    <PARAM NAME = "Ss7_Y" VALUE = "106700">
    <PARAM NAME = "Ss8_X" VALUE = "229857">
    <PARAM NAME = "Ss8_Y" VALUE = "70900">
    <PARAM NAME = "Ss9_X" VALUE = "181714">
45  <PARAM NAME = "Ss9_Y" VALUE = "70900">
    <PARAM NAME = "Ss10_X" VALUE = "133571">
    <PARAM NAME = "Ss10_Y" VALUE = "70900">
    <PARAM NAME = "Ss11_X" VALUE = "85428">
    <PARAM NAME = "Ss11_Y" VALUE = "70900">
50  <PARAM NAME = "Ss12_X" VALUE = "37285">
    <PARAM NAME = "Ss12_Y" VALUE = "70900">
    <PARAM NAME = "Ss13_X" VALUE = "-10858">
    <PARAM NAME = "Ss13_Y" VALUE = "70900">
    <PARAM NAME = "Ss14_X" VALUE = "-10858">
55  <PARAM NAME = "Ss14_Y" VALUE = "35100">

```

- 35 -

```

    <PARAM NAME = "Ss15_X" VALUE = "37285">
    <PARAM NAME = "Ss15_Y" VALUE = "35100">
    <PARAM NAME = "Ss16_X" VALUE = "85428">
    <PARAM NAME = "Ss16_Y" VALUE = "35100">
5    <PARAM NAME = "Ss17_X" VALUE = "133571">
    <PARAM NAME = "Ss17_Y" VALUE = "35100">
    <PARAM NAME = "Ss18_X" VALUE = "181714">
    <PARAM NAME = "Ss18_Y" VALUE = "35100">
    <PARAM NAME = "Ss19_X" VALUE = "229857">
10   <PARAM NAME = "Ss19_Y" VALUE = "35100">
    <PARAM NAME = "Ss20_X" VALUE = "278000">
    <PARAM NAME = "Ss20_Y" VALUE = "-700">
    <PARAM NAME = "Ss21_X" VALUE = "229857">
    <PARAM NAME = "Ss21_Y" VALUE = "-700">
15   <PARAM NAME = "Ss22_X" VALUE = "181714">
    <PARAM NAME = "Ss22_Y" VALUE = "-700">
    <PARAM NAME = "Ss23_X" VALUE = "133571">
    <PARAM NAME = "Ss23_Y" VALUE = "-700">
    <PARAM NAME = "Ss24_X" VALUE = "85428">
20   <PARAM NAME = "Ss24_Y" VALUE = "-700">
    <PARAM NAME = "Ss25_X" VALUE = "37285">
    <PARAM NAME = "Ss25_Y" VALUE = "-700">
    <PARAM NAME = "Ss26_X" VALUE = "-10858">
    <PARAM NAME = "Ss26_Y" VALUE = "-700">
25   <PARAM NAME = "Ss27_X" VALUE = "-10858">
    <PARAM NAME = "Ss27_Y" VALUE = "-36500">
    <PARAM NAME = "Ss28_X" VALUE = "37285">
    <PARAM NAME = "Ss28_Y" VALUE = "-36500">
    <PARAM NAME = "Ss29_X" VALUE = "85428">
30   <PARAM NAME = "Ss29_Y" VALUE = "-36500">
    <PARAM NAME = "Ss30_X" VALUE = "133571">
    <PARAM NAME = "Ss30_Y" VALUE = "-36500">
    <PARAM NAME = "Ss31_X" VALUE = "181714">
    <PARAM NAME = "Ss31_Y" VALUE = "-36500">
35   <PARAM NAME = "Ss32_X" VALUE = "229857">
    <PARAM NAME = "Ss32_Y" VALUE = "-36500">
    <PARAM NAME = "Ss33_X" VALUE = "278000">
    <PARAM NAME = "Ss33_Y" VALUE = "-36500">
    <PARAM NAME = "Ss34_X" VALUE = "278000">
40   <PARAM NAME = "Ss34_Y" VALUE = "-72300">
    <PARAM NAME = "Ss35_X" VALUE = "229857">
    <PARAM NAME = "Ss35_Y" VALUE = "-72300">
    <PARAM NAME = "Ss36_X" VALUE = "181714">
    <PARAM NAME = "Ss36_Y" VALUE = "-72300">
45   <PARAM NAME = "Ss37_X" VALUE = "133571">
    <PARAM NAME = "Ss37_Y" VALUE = "-72300">
    <PARAM NAME = "Da0_X" VALUE = "214532">
    <PARAM NAME = "Da0_Y" VALUE = "65584">
    <PARAM NAME = "Da1_X" VALUE = "212996">
50   <PARAM NAME = "Da1_Y" VALUE = "65584">
    <PARAM NAME = "Da2_X" VALUE = "211460">
    <PARAM NAME = "Da2_Y" VALUE = "65584">
    <PARAM NAME = "Da3_X" VALUE = "209924">
    <PARAM NAME = "Da3_Y" VALUE = "65584">
55   <PARAM NAME = "Da4_X" VALUE = "208388">

```

-36-

```

5  <PARAM NAME = "Da4_Y" VALUE = "65584">
    <PARAM NAME = "Da5_X" VALUE = "206852">
    <PARAM NAME = "Da5_Y" VALUE = "65584">
    <PARAM NAME = "Da6_X" VALUE = "205316">
    <PARAM NAME = "Da6_Y" VALUE = "65584">
    <PARAM NAME = "Da7_X" VALUE = "203780">
    <PARAM NAME = "Da7_Y" VALUE = "65584">
    <PARAM NAME = "Da8_X" VALUE = "214532">
    <PARAM NAME = "Da8_Y" VALUE = "64400">
10  <PARAM NAME = "Da9_X" VALUE = "212996">
    <PARAM NAME = "Da9_Y" VALUE = "64400">
    <PARAM NAME = "Da10_X" VALUE = "211460">
    <PARAM NAME = "Da10_Y" VALUE = "64400">
    <PARAM NAME = "Da11_X" VALUE = "209924">
15  <PARAM NAME = "Da11_Y" VALUE = "64400">
    <PARAM NAME = "Da12_X" VALUE = "208388">
    <PARAM NAME = "Da12_Y" VALUE = "64400">
    <PARAM NAME = "Da13_X" VALUE = "206852">
    <PARAM NAME = "Da13_Y" VALUE = "64400">
20  <PARAM NAME = "Da14_X" VALUE = "205316">
    <PARAM NAME = "Da14_Y" VALUE = "64400">
    <PARAM NAME = "Da15_X" VALUE = "203780">
    <PARAM NAME = "Da15_Y" VALUE = "64400">
    <PARAM NAME = "Da16_X" VALUE = "214532">
25  <PARAM NAME = "Da16_Y" VALUE = "63216">
    <PARAM NAME = "Da17_X" VALUE = "212996">
    <PARAM NAME = "Da17_Y" VALUE = "63216">
    <PARAM NAME = "Da18_X" VALUE = "211460">
    <PARAM NAME = "Da18_Y" VALUE = "63216">
30  <PARAM NAME = "Da19_X" VALUE = "209924">
    <PARAM NAME = "Da19_Y" VALUE = "63216">
    <PARAM NAME = "Da20_X" VALUE = "208388">
    <PARAM NAME = "Da20_Y" VALUE = "63216">
    <PARAM NAME = "Da21_X" VALUE = "206852">
35  <PARAM NAME = "Da21_Y" VALUE = "63216">
    <PARAM NAME = "Da22_X" VALUE = "205316">
    <PARAM NAME = "Da22_Y" VALUE = "63216">
    <PARAM NAME = "Da23_X" VALUE = "203780">
    <PARAM NAME = "Da23_Y" VALUE = "63216">
40  <PARAM NAME = "Da24_X" VALUE = "214532">
    <PARAM NAME = "Da24_Y" VALUE = "62032">
    <PARAM NAME = "Da25_X" VALUE = "212996">
    <PARAM NAME = "Da25_Y" VALUE = "62032">
    <PARAM NAME = "Da26_X" VALUE = "211460">
45  <PARAM NAME = "Da26_Y" VALUE = "62032">
    <PARAM NAME = "Da27_X" VALUE = "209924">
    <PARAM NAME = "Da27_Y" VALUE = "62032">
    <PARAM NAME = "Da28_X" VALUE = "208388">
    <PARAM NAME = "Da28_Y" VALUE = "62032">
50  <PARAM NAME = "Da29_X" VALUE = "206852">
    <PARAM NAME = "Da29_Y" VALUE = "62032">
    <PARAM NAME = "Da30_X" VALUE = "205316">
    <PARAM NAME = "Da30_Y" VALUE = "62032">
    <PARAM NAME = "Da31_X" VALUE = "203780">
55  <PARAM NAME = "Da31_Y" VALUE = "62032">

```

-37-

```

5  <PARAM NAME = "Da32_X" VALUE = "214532">
    <PARAM NAME = "Da32_Y" VALUE = "60848">
    <PARAM NAME = "Da33_X" VALUE = "212996">
    <PARAM NAME = "Da33_Y" VALUE = "60848">
    <PARAM NAME = "Da34_X" VALUE = "211460">
    <PARAM NAME = "Da34_Y" VALUE = "60848">
    <PARAM NAME = "Da35_X" VALUE = "209924">
    <PARAM NAME = "Da35_Y" VALUE = "60848">
10  <PARAM NAME = "Da36_X" VALUE = "208388">
    <PARAM NAME = "Da36_Y" VALUE = "60848">
    <PARAM NAME = "Da37_X" VALUE = "206852">
    <PARAM NAME = "Da37_Y" VALUE = "60848">
    <PARAM NAME = "Da38_X" VALUE = "205316">
    <PARAM NAME = "Da38_Y" VALUE = "60848">
15  <PARAM NAME = "Da39_X" VALUE = "203780">
    <PARAM NAME = "Da39_Y" VALUE = "60848">
    <PARAM NAME = "Da40_X" VALUE = "214532">
    <PARAM NAME = "Da40_Y" VALUE = "59664">
    <PARAM NAME = "Da41_X" VALUE = "212996">
20  <PARAM NAME = "Da41_Y" VALUE = "59664">
    <PARAM NAME = "Da42_X" VALUE = "211460">
    <PARAM NAME = "Da42_Y" VALUE = "59664">
    <PARAM NAME = "Da43_X" VALUE = "209924">
    <PARAM NAME = "Da43_Y" VALUE = "59664">
25  <PARAM NAME = "Da44_X" VALUE = "208388">
    <PARAM NAME = "Da44_Y" VALUE = "59664">
    <PARAM NAME = "Da45_X" VALUE = "206852">
    <PARAM NAME = "Da45_Y" VALUE = "59664">
    <PARAM NAME = "Da46_X" VALUE = "205316">
30  <PARAM NAME = "Da46_Y" VALUE = "59664">
    <PARAM NAME = "Da47_X" VALUE = "203780">
    <PARAM NAME = "Da47_Y" VALUE = "59664">
    <PARAM NAME = "Da48_X" VALUE = "214532">
    <PARAM NAME = "Da48_Y" VALUE = "58480">
35  <PARAM NAME = "Da49_X" VALUE = "212996">
    <PARAM NAME = "Da49_Y" VALUE = "58480">
    <PARAM NAME = "Da50_X" VALUE = "211460">
    <PARAM NAME = "Da50_Y" VALUE = "58480">
    <PARAM NAME = "Da51_X" VALUE = "209924">
40  <PARAM NAME = "Da51_Y" VALUE = "58480">
    <PARAM NAME = "Da52_X" VALUE = "208388">
    <PARAM NAME = "Da52_Y" VALUE = "58480">
    <PARAM NAME = "Da53_X" VALUE = "206852">
    <PARAM NAME = "Da53_Y" VALUE = "58480">
45  <PARAM NAME = "Da54_X" VALUE = "205316">
    <PARAM NAME = "Da54_Y" VALUE = "58480">
    <PARAM NAME = "Da55_X" VALUE = "203780">
    <PARAM NAME = "Da55_Y" VALUE = "58480">
    <PARAM NAME = "Da56_X" VALUE = "180740">
50  <PARAM NAME = "Da56_Y" VALUE = "82160">
    <PARAM NAME = "Da57_X" VALUE = "179204">
    <PARAM NAME = "Da57_Y" VALUE = "82160">
    <PARAM NAME = "Da58_X" VALUE = "177668">
    <PARAM NAME = "Da58_Y" VALUE = "82160">
55  <PARAM NAME = "Da59_X" VALUE = "176132">

```

-38-

```

    <PARAM NAME = "Da59_Y" VALUE = "82160">
    <PARAM NAME = "Da60_X" VALUE = "174596">
    <PARAM NAME = "Da60_Y" VALUE = "82160">
    <PARAM NAME = "Da61_X" VALUE = "173060">
5   <PARAM NAME = "Da61_Y" VALUE = "82160">
    <PARAM NAME = "Da62_X" VALUE = "171524">
    <PARAM NAME = "Da62_Y" VALUE = "82160">
    <PARAM NAME = "Da63_X" VALUE = "180740">
    <PARAM NAME = "Da63_Y" VALUE = "80976">
10  <PARAM NAME = "Da64_X" VALUE = "179204">
    <PARAM NAME = "Da64_Y" VALUE = "80976">
    <PARAM NAME = "Da65_X" VALUE = "177668">
    <PARAM NAME = "Da65_Y" VALUE = "80976">
    <PARAM NAME = "Da66_X" VALUE = "176132">
15  <PARAM NAME = "Da66_Y" VALUE = "80976">
    <PARAM NAME = "Da67_X" VALUE = "174596">
    <PARAM NAME = "Da67_Y" VALUE = "80976">
    <PARAM NAME = "Da68_X" VALUE = "173060">
    <PARAM NAME = "Da68_Y" VALUE = "80976">
20  <PARAM NAME = "Da69_X" VALUE = "171524">
    <PARAM NAME = "Da69_Y" VALUE = "80976">
    <PARAM NAME = "Da70_X" VALUE = "180740">
    <PARAM NAME = "Da70_Y" VALUE = "79792">
    <PARAM NAME = "Da71_X" VALUE = "179204">
25  <PARAM NAME = "Da71_Y" VALUE = "79792">
    <PARAM NAME = "Da72_X" VALUE = "177668">
    <PARAM NAME = "Da72_Y" VALUE = "79792">
    <PARAM NAME = "Da73_X" VALUE = "176132">
    <PARAM NAME = "Da73_Y" VALUE = "79792">
30  <PARAM NAME = "Da74_X" VALUE = "174596">
    <PARAM NAME = "Da74_Y" VALUE = "79792">
    <PARAM NAME = "Da75_X" VALUE = "173060">
    <PARAM NAME = "Da75_Y" VALUE = "79792">
    <PARAM NAME = "Da76_X" VALUE = "171524">
35  <PARAM NAME = "Da76_Y" VALUE = "79792">
    <PARAM NAME = "Da77_X" VALUE = "180740">
    <PARAM NAME = "Da77_Y" VALUE = "78608">
    <PARAM NAME = "Da78_X" VALUE = "179204">
    <PARAM NAME = "Da78_Y" VALUE = "78608">
40  <PARAM NAME = "Da79_X" VALUE = "177668">
    <PARAM NAME = "Da79_Y" VALUE = "78608">
    <PARAM NAME = "Da80_X" VALUE = "176132">
    <PARAM NAME = "Da80_Y" VALUE = "78608">
    <PARAM NAME = "Da81_X" VALUE = "174596">
45  <PARAM NAME = "Da81_Y" VALUE = "78608">
    <PARAM NAME = "Da82_X" VALUE = "173060">
    <PARAM NAME = "Da82_Y" VALUE = "78608">
    <PARAM NAME = "Da83_X" VALUE = "171524">
    <PARAM NAME = "Da83_Y" VALUE = "78608">
50  <PARAM NAME = "Da84_X" VALUE = "180740">
    <PARAM NAME = "Da84_Y" VALUE = "77424">
    <PARAM NAME = "Da85_X" VALUE = "179204">
    <PARAM NAME = "Da85_Y" VALUE = "77424">
    <PARAM NAME = "Da86_X" VALUE = "177668">
55  <PARAM NAME = "Da86_Y" VALUE = "77424">

```


- 39 -

```
<PARAM NAME = "Da87_X" VALUE = "176132">
<PARAM NAME = "Da87_Y" VALUE = "77424">
<PARAM NAME = "Da88_X" VALUE = "174596">
<PARAM NAME = "Da88_Y" VALUE = "77424">
5 <PARAM NAME = "Da89_X" VALUE = "173060">
  <PARAM NAME = "Da89_Y" VALUE = "77424">
  <PARAM NAME = "Da90_X" VALUE = "171524">
  <PARAM NAME = "Da90_Y" VALUE = "77424">
  <PARAM NAME = "Da91_X" VALUE = "180740">
10 <PARAM NAME = "Da91_Y" VALUE = "76240">
  <PARAM NAME = "Da92_X" VALUE = "179204">
  <PARAM NAME = "Da92_Y" VALUE = "76240">
  <PARAM NAME = "Da93_X" VALUE = "177668">
  <PARAM NAME = "Da93_Y" VALUE = "76240">
15 <PARAM NAME = "Da94_X" VALUE = "176132">
  <PARAM NAME = "Da94_Y" VALUE = "76240">
  <PARAM NAME = "Da95_X" VALUE = "174596">
  <PARAM NAME = "Da95_Y" VALUE = "76240">
  <PARAM NAME = "Da96_X" VALUE = "173060">
20 <PARAM NAME = "Da96_Y" VALUE = "76240">
  <PARAM NAME = "Da97_X" VALUE = "171524">
  <PARAM NAME = "Da97_Y" VALUE = "76240">
  <PARAM NAME = "Da98_X" VALUE = "180740">
  <PARAM NAME = "Da98_Y" VALUE = "75056">
25 <PARAM NAME = "Da99_X" VALUE = "179204">
  <PARAM NAME = "Da99_Y" VALUE = "75056">
  <PARAM NAME = "Da100_X" VALUE = "177668">
  <PARAM NAME = "Da100_Y" VALUE = "75056">
  <PARAM NAME = "Da101_X" VALUE = "176132">
30 <PARAM NAME = "Da101_Y" VALUE = "75056">
  <PARAM NAME = "Da102_X" VALUE = "174596">
  <PARAM NAME = "Da102_Y" VALUE = "75056">
  <PARAM NAME = "Da103_X" VALUE = "173060">
  <PARAM NAME = "Da103_Y" VALUE = "75056">
35 <PARAM NAME = "Da104_X" VALUE = "171524">
  <PARAM NAME = "Da104_Y" VALUE = "75056">
</APPLET>
</BODY>
</HTML>
```

-40-

Referring now to the drawings, and especially to FIGS. 9A, 9B and 10, apparatus for synthesizing low magnification and high magnification microscopic images is shown therein and generally identified by reference numeral 10. The system includes a computer 12 which is a dual Pentium Pro personal computer in combination with a Hitachi HV-C20 video camera 14 associated with a Zeiss Axioplan 2 microscope 16. The computer system 12 is able to receive signals from the camera 14 which captures light from the microscope 16 having a microscope slide 18 positioned on an LUDL encoded motorized stage 20. The encoded motorized stage 20 includes a MAC 2000 stage controller for controlling the stage in response to the computer 12. A microscope slide 18 includes a biological specimen 21 which is to be viewed by the microscope and whose image is to be digitized both at low magnification and at high magnification as selected by a user. The low magnification digitized image is then displayed on a 21 inch Iiyama video display monitor 22 having resolution of 1600 by 1200 to provide display screens of the type shown in FIGS. 1 through 3 including a low magnification image 24, for instance, at 1.25 power, a high magnification image 26, for instance at 40X power and a control window or image 28. The low magnification image may have identified therein a region 30 which is reproduced at high magnification in high magnification screen or window 26 so that a pathologist or other operator of the system can review architectural regions of interest in low magnification image 24 and simultaneously view them in high magnification in the high magnification screen or window 26 to determine whether the cells forming a portion of the architectural feature need be examined further for cancer or the like or not.

The computer 10 is constructed around a PCI system bus 40 and has a first Pentium Pro microprocessor 42 and a second pentium pro microprocessor 44 connected thereto. The system bus 40 has connected to it a PCI bus

-41-

50 and an ISA bus 52. The PCI bus 50 has a SCSI controller 60 connected thereto to send and receive information from a hard disk 62. The hard disk 62 also is coupled in daisy chain SCSI fashion to a high capacity removal disk and to a CD Rom drive 66. The hard disks 62 contains the programs for operating the system for controlling the microscope 16 and for processing the images as well as for doing a quantitative analysis of the selected portions of the histological specimens being viewed on the slide 18. The system bus 40 also has connected to it a random access memory 70 within which portions of the program being executed are stored as well as a read only memory 72 for holding a bootstrap loader as well as portions of the basic input/output operating system. A floppy disk controller 74 is coupled to the system bus 40 and has connected to it a floppy disk drive 76 for reading and writing information to a floppy disk as appropriate. A mouse controller 80 is coupled to the system bus and has a mouse 82 which operates as a pointing device for controlling manipulations on the screen 22 and within the windows 24, 26 and 28. A keyboard controller 90 is connected to the system bus and has a keyboard 92 connected thereto. The keyboard 92 may be used to send and receive alpha numeric signals to other portions of the computer. An audio controller 100 has a plurality of speakers 102 and a microphone 104 connected thereto for audio input and output and is coupled to the system bus 40. A network interface, such as a network interface card 104, is connected to the system bus and can provide signals via a channel 106 to other portions of a network or internet to which the system may be connected. Likewise, signals can be sent out of the system through a modem 110 connected to the ISA bus 52 and may be sent via a channel 112, for instance, to the internet. A printer 116 is connected via a parallel I/O controller 118 to the system bus in order to provide printouts as appropriate of screens and

-42-

other information as it is generated. A serial I/O controller 122 is connected to the system bus and has connected to it a camera controller 124 which is coupled to CCD sensors 126 in the cameras. The CCD sensors 126
5 supply pixel or image signals representative of what is found on the slide 18 to an Epix pixci image acquisition controller 130 coupled to the PCI bus 50.

The microscope 16 includes a base 140 having a stage 20 positioned thereon as well as an objective
10 turret 142 having a plurality of objectives 144, 146 and 148 thereon. The objective 144, for instance, may be of 1.25x objective. The objective 146 may be a 20X objective. The objective 148 may be a 40X objective. Signals from the camera sensors and controller are
15 supplied over a bus 128 to the image acquisition system where they are digitized and supplied to the PCI bus for storage in RAM or for backing storage on the hard disk 62.

When a specimen is on the slide 18 the stage 20
20 may be manipulated under the control of the computer through a stage controller 160 coupled to the serial I/O controller 122. Likewise, a microscope controller 162 controls aspects of the microscope such as the illumination, the color temperature or spectral output of
25 a lamp 168 and the like. For instance, in normal operation, when a specimen is placed on the slide, specimen slide 18 is placed on the stage 20 in a step 200, as shown in FIG. 14, the processors 42 or 44 send a command through the system bus to cause the serial I/O
30 controller 122 to signal the microscope controller to change magnification to 1.25X in a step 202. This is done by rotating the objective turret of the Axioplan 2 microscope to select the objective 144. Likewise, the controller sets the color temperature of the lamp 168,
35 sets a pair of neutral density filter wheels 170 and 172 and sets a field diaphragm 174 for the correct illumination. A condenser diaphragm 176 is also

-43-

controlled and a color filter wheel 180 may also be controlled to apply the appropriate filter color to the CCD sensors 126 in the camera. The entire slide is then scanned in a step 204. The images are tiled and melded
5 together into the overall image 24 supplied on the screen 22 to provide the operator in the step 206 with a visually inspectable macro image of relevant regions of the slide of interest.

In order to provide the magnified image, the
10 mouse may be moved to identify a marker segment or region which, for instance, may be a rectangular region which will cause the microscope to change magnification as at step 208 to 4x, 20x, 40x, etc., by rotating the turret to bring the appropriate objective lens system into viewing
15 position.

Next the user, in a step 209a, uses the mouse to select the region on the macro image in order to select the micro image to be viewed on the screen 22. In a step 209b a test is made to determine whether the user has
20 commanded continued inspection. If the user has, a test is made in a step 209c to determine if the magnification is to be changed by changing the selected objective. In the event the magnification is to be changed control is transferred to the step 208. If the magnification is to
25 remain unchanged control is transferred to the step 209a. In the event inspection is not to continue the region selected is outlined for higher magnification scan in a step 209d. In a step 209e, a command may be received to scan or acquire the higher magnification image for
30 display in screen 26. The image may then be archived for later analysis, displayed or analyzed immediately.

In order to perform the magnification called for in step 208, the overall illumination and control of the microscope will be controlled so that in a step 210 the
35 objective turret 142 will be rotated to place the higher power objective above the slide 18. In a step 212 voltage to the lamp will be changed to adjust the lamp

-44-

168 to provide the proper illumination and color temperature as predetermined for the selected objective. In a step 214, the condenser diaphragm 176 will have its opening selected as appropriate to provide the proper
5 illumination for that objective. In a step 216, the filter turret 180 will select the proper light wavelength filter to be supplied to the camera sensors. For instance, a red, blue or green filter, as appropriate, particularly if the specimen has been stained. In a step
10 218 the field diaphragm 174 will have its opening changed. In a step 220 the neutral density filter wheel 170 will select a neutral density filter and in a step 222 the neutral density filter wheel 172 will also select a neutral density filter. In a step 224 the X, Y and Z
15 offsets will be used for reconstruction of the recorded image at the magnification and in a step 226 the current position will be read from encoders in the stage which are accurate to .10 micron.

In order to identify the selected region the
20 mouse is moved to that area of the region in a pointing operation in a step 240 as shown in FIG. 14. The mouse may be moved to draw a box around the region selected. In a step 242 the X and Y screen points are computed for the edges of the regions selected and the computed image
25 or pixel points are translated to stage coordinate points in order to control the stage of the microscope. In a step 244 a list of all of the X fields for positioning the stage for the objective is stored in random access memory and may be backed up on the hard disk. The
30 information from the X offsets for the objective and the stage offsets is used as well as the size of the field to position the slide properly under the objective to capture the micro image.

When the slide has been positioned properly, as
35 shown in FIG. 15 in a step 250 the stage is positioned for each of the X and Y coordinate values in stage coordinate values and the digitized image is captured by

-45-

the cameras and stored in RAM and backed up on the hard disk. The image may be then analyzed quantitatively in various manners such as those set forth in the previously-identified United States application.

- 5 Optionally the image may be stored for archival purposes in a step 254.

In order to override the specific control functions that take place as shown in FIG. 12, a screen is provided as shown in FIG. 13 wherein the X-Y step size
10 can be edited, the X, Y and Z offset can be edited, the lamp voltage can be selected, the neutral density filter can be selected as well as the opening of the field diaphragm and several other microscopic characteristics. FIG. 13 is a view of the settings of the microscope
15 objective properties of the Axioplan 2, computer-controlled microscope.

The X and Y positioning is specifically carried out as shown in FIG. 16 where the slide 18 is shown with a slide boundary 270, 272, 274 and 276. Stage boundary
20 for limits of the stage travel for purposes of the stage the stage can be moved all the way from an upper left hand corner of travel 276 to a lower right hand corner of travel 280. At the upper left hand bounded corner of travel 278 limits which a signal that the end of travel
25 has been reached and the stage is then translated a short distance 282 in the extra action and a short distance 284 in the Y direction to define the first tile 288 in terms of a reference point 290 at its upper left hand corner. Since the size of the macro image tile 288 is known, the
30 next macro image tile 292 may be placed contiguous with it by moving the stage appropriately and by measuring the location of the stage from the stage in counters without the necessity of performing any image manipulation. The image tiles 288 and 292 may be abutted without any
35 substantial overlap or they may be overlapped slightly, such as a one pixel with overlap, which is negligible insofar as blurring of any adjacent edges of abutted

-46-

image tiles. The upper left hand corner 300 of the tile 292 defines the rest of 292 and other tiles can be so defined. Micro image tiles can likewise be defined so that they are contiguous but not substantially
5 overlapping, as would interfere with the composite image. This avoids the problems encountered with having to perform extended computations on digital images in a frame storer or multiple frame storage in order to match or bring the images into contiguity without blurriness at
10 the edges of contiguous image tiles. It may be appreciated that the low power image 24 has a plurality of micro images defined therein which are tiled and which are shown in higher magnification as individual tiles 312, 314, 316 and the like. In addition, the region 310
15 when magnified as shown in the window 26 may exceed the bounds of the window and thus the window may include scroll bars or other means for allowing the image 310 which is larger than the window 26 to be examined from within the window 26.

20 The stage 200 is best seen in FIG. 16A and includes the X and Y stepper motors 279 and 281 with their respective encoders, which provide a closed loop system to give the .1 micron accuracy versus the usual 5 or 6 micron accuracy of most microscope stages without a
25 closed loop system. This closed loop system and this very high accuracy allow the abutting of the tile images for both high magnification and low magnification images without the substantial overlap and the time-consuming and expensive software currently used to eliminate the
30 overlap and blurriness at the overlapping edges of adjacent image tiles. With the precisely positioned stage and by using the tiling system described in connection with FIG. 16, where the slide is precisely positioned relative to a center point CP for the slide,
35 and the known position of point 278 is always taken from the same point, the tiles may be positioned precisely in a horizontal row and precisely in vertical rows to

-47-

reconstruct the macro image and the micro image. This reconstruction is done without the use, as in the prior art, of extensive software manipulation to eliminate overlapping image tiles, horizontally or vertically or
5 the haphazard orientation of image tiles.

The present invention also includes the facility for allowing remote observation to occur by being able to couple the system either over a network communication facility to an intranet, for instance via the network
10 interface, or via a modem or other suitable connection, to an internet so that once the image has been scanned and stored in memory on hard disks or other storage, remote users may be able to access the low magnification image as well as the high magnification image and move
15 around within both images to make determinations as to the histological characteristics of the samples.

An additional feature of the system includes a plurality of networked workstations coupled to a first computer console 12 having a display screen 22 connected
20 to the microscope 14. Satellite work stations 350 and 352 are substantially identical to the work station 12 including respective computers 354 and 356 coupled to displays 358 and 360. The devices can be manipulated through input devices 360 and 362 which may include a
25 keyboard, mouse and the like. Also a third device can be connected including a work station 370, having a display 372, a computer 374 and an input device 376. Each of the devices is connected over respective network lines 380, 382, 384 to the computer 12 which transmission may be via
30 either net or the like. Each of the different operators at the physically separate viewing stations can locate regions from the view of entire tissue cross sections via a macro view and label the regions for subsequent scanning and/or quantitative analysis. A single operator
35 at the instrument station 12 can locate regions to view the entire tissue cross section. Those regions can be labeled for subsequent scanning and/or quantitative

-48-

analysis with subsequent review and physically remote viewing stations, for instance, in an operating room or in individual pathologists' signout areas in order to review analysis results while still maintaining and
5 reviewing the entire macro view of the tissue and/or the individual stored images from which the quantitative results were obtained. The viewing stations 350, 352 and 370 can comprise desk top computers, laptops, etc. There is no need for a microscope at the network stations 350,
10 352 and 370.

In a still further alternative embodiment, remote workstations 400, 402, 404, 406 and 408 may be connected through a server 410 which may be supplied via a packet switched network. The server 410 and may be a
15 hypertext transport protocol based server of the type used for the World Wide Web or may be a telnet type server as used previously in internet remote operation applications. The server 410 communicates via a communications channel 414 with a local computer 416
20 having a display 418 associated therewith, the local computer 416 being connected to the microscope 420. Each of the remote work stations 400, 402, 404, 406 and 408 may perform the same operations as the stations 350, 352 and 370 although they do it from nearby buildings or even
25 from around the world, thus providing additional flexibility for others to make use of the specimen obtained and being viewed under the microscope 420. In addition, stored images may be disseminated through the server 410 to the remote servers 400 through 408 for
30 further analysis and review.

While there has been illustrated and described a particular embodiment of the present invention, it will be appreciated that numerous changes and modifications will occur to those skilled in the art, and it is
35 intended in the appended claims to cover all those changes and modifications which followed in the true spirit and scope of the present invention.

-49-

What Is Claimed Is:

1. A data structure of images taken from a specimen on a microscope slide comprising:

5 a first series of contiguous, multiple images at a first magnification abutted against each other to create an overall low resolution view of several adjacent, original microscope images assembled together;

the first series of multiple images taken from at least a portion of a specimen on the slide;

10 a second series of contiguous, multiple images at a second higher magnification abutted against each other to create a high resolution view of several adjacent, original microscope images assembled together, taken from said portion of the specimen; and

15 the first and second series of images providing multiple resolution images of the slide specimen to a viewer.

2. A data structure in accordance with Claim 1 wherein each of the series of contiguous, multiple images
20 corresponds to an optical image seen by a person through an objective lens of a microscope.

3. A data structure in accordance with Claim 1 wherein each of the series of contiguous, multiple images comprises a compressed image using a reduced percentage
25 of a corresponding original microscope image.

4. A data structure in accordance with Claim 1 wherein an addressable coordinate system is provided for the first and second magnification images so that the higher magnification images can be easily located with
30 respect to the lower magnification images.

5. The data structure of Claim 4 wherein each of the image tiles in the first series and in the second

-50-

series includes coordinate information for enabling reconstruction of the entire image.

6. The data structure of Claim 4 further comprising a dynamic, self-executing program for viewing,
5 manipulating and reconstructing the image tiles to form the low and high resolution images.

7. The data structure of Claim 5 further comprising a dynamic, self-executing program for viewing,
manipulating and reconstructing the image tiles to form
10 the low and high resolution images.

8. The data structure of Claim 7 wherein said self-executing program comprises a Java applet.

9. The data structure of Claim 7 wherein said self-executing program comprises an Active-X applet.

15 10. The data structure of Claim 7 wherein said self-executing program comprises an Internet web browser.

11. The data structure of Claim 7 wherein said self-executing program comprises an intranet browser.

12. The data structure of Claim 7 further
20 comprising means for scrolling through said first digital image wherein selection of a point and a region on said first digital image displays a corresponding image at said second magnification in said second digital image.

13. The data structure of Claim 7 wherein said
25 program includes means for displaying the coordinates of a point on said first image and said second image.

14. A storage medium having digitized images of a specimen on a microscope slide comprising:

-51-

a storage medium;
a first series of contiguous, multiple images at
a first magnification abutted against each other to
create an overall low resolution view of several
5 adjacent, original microscope images assembled together;
the first series of multiple images taken from
at least a portion of a specimen on the slide;
a second series of contiguous, multiple images
at a second higher magnification abutted against each
10 other to create a high resolution view of several
adjacent, original microscope images assembled together,
taken from said portion of the specimen; and
the first and second series of images providing
multiple resolution images of the slide specimen to a
15 viewer.

15. A storage medium in accordance with Claim
14 wherein each of the series of contiguous, multiple
images corresponds to an optical image seen by a person
through an objective lens of a microscope.

20 16. A storage medium in accordance with Claim
14 wherein each of the series of contiguous, multiple
images comprises a compressed image using a reduced
percentage of a corresponding original microscope image.

25 17. A storage medium in accordance with Claim
14 wherein an addressable coordinate system is provided
for the first and second magnification images so that the
higher magnification images can be easily located with
respect to the lower magnification images.

30 18. The storage medium of Claim 14 wherein each
of the image tiles in the first series and in the second
series includes coordinate information for enabling
reconstruction of the entire image.

-52-

19. The storage medium of Claim 14 further comprising a dynamic, self-executing program for viewing, manipulating and reconstructing the image tiles.

20. The storage medium of Claim 14 further
5 comprising a dynamic, self-executing program for viewing, manipulating and reconstructing the image tiles.

21. The storage medium of Claim 20 wherein said self-executing program comprises a Java applet.

22. The storage medium of Claim 20 wherein said
10 self-executing program comprises an Active-X applet.

23. The storage medium of Claim 20 wherein said self-executing program comprises an Internet web browser.

24. The storage medium of Claim 20 wherein said self-executing program comprises an intranet browser.

15 25. The storage medium of Claim 20 further comprising means for scrolling through said first digital image wherein selection of a point and a region on said first digital image displays a corresponding image at said second magnification in said second digital image.

20 26. The storage medium of Claim 20 wherein said program includes means for displaying the coordinates of a point on said first image and said second image.

27. The storage medium of Claim 14 wherein the storage medium is selected from the group of CD-rom disks
25 and Jazz drive disks.

28. A method of constructing a data structure taken from a specimen on a microscope slide comprising the steps of:

-53-

digitally scanning and storing a first series of digitized images taken from a portion of a specimen on a microscope slide in a first series of contiguous image tiles at a first magnification to allow formation of an
5 overall view;

digitally scanning and storing a second series of digitized images taken from the portion of the specimen on the microscope slide in a second series of contiguous image tiles at a second, higher magnification;
10 and

providing the data structure with the first and second series of digitized, stored images to provide a user with multiple resolution images from the specimen.

29. The method of Claim 28 further comprising
15 the step of:

providing the data structure with a dynamic, self-executing program effective for viewing, manipulating and reconstructing the image tiles.

30. The method of Claim 28 further comprising
20 the step of:

providing each of the image tiles in the first series and in the second series with coordinate information for enabling reconstruction of the first and second images.

25 31. The method of Claim 30 wherein said self-executing program comprises the step of providing a Java applet.

32. The method of Claim 30 further comprising the step of displaying the X-Y coordinates of a selected
30 point on the first and second image.

-54-

33. The method of Claim 28 further comprising the steps of compressing the digitized images and storing the compressed digitized images.

34. The method of Claim 28 wherein the step of
5 digitizing and storing the images comprises:
using a higher resolution central portion of
optical images taken through the microscope; and
discarding fuzzy outer portions of the optical
image.

10 35. The method of Claim 28 wherein each of the
digitized images of the series corresponds to
substantially an optical view as seen by a person through
an objective lens of the microscope.

36. A storage medium having digitized images
15 from a specimen on a piece on a microscopic support
comprising:
a storage medium;
a first collection of digitized image fields of
view at a first magnification coherently stored on the
20 storage medium to provide an overall low resolution view
from original microscope images of the specimen on the
slide taken at a first resolution;
a collection of digitized image fields of view
at a higher magnification coherently stored on the
25 storage medium to provide a higher resolution image for
viewing from a selected portion of the overall view; and
a control program stored with the first and
second collection of digitized images fields to allow a
user to move back and forth between the overall view at
30 the first lower resolution and the selected higher
resolution images.

37. A storage medium in accordance with Claim
36 wherein the first collection of single image fields

-55-

comprises a collection of tiled images abutted one against the other.

38. A storage medium in accordance with Claim 37 wherein one tile is one picture viewed through the
5 microscope.

39. A storage medium in accordance with Claim 38 wherein the second collection of image fields comprises at least three higher resolution image fields of view, each having a substantially different resolution
10 and each capable of being selected by a user.

40. A storage medium in accordance with Claim 39 wherein the storage medium is on a web browser and the view is accessing the browser for viewing the specimen's digitized images.

15 41. A storage medium in accordance with Claim 40 wherein the stored, digitized images are JPEG images received over the Internet; and
the stored control program comprises a HTML file and an active, self-executing program.

20 42. A storage medium in accordance with Claim 36 wherein the storage medium is a CD-Rom.

43. A storage medium in accordance with Claim 41 wherein the active, self-executing program comprises a Java applet.

25 44. A method of constructing and using a self-executing data structure of an image of a specimen on a microscope slide comprising:

digitally scanning and storing multiple magnification and multiple resolution images from the
30 specimen on a microscope slide to create a plurality of

-56-

individual image tiles having multiple magnifications and multiple resolutions;

providing a dynamic, self-executing program on the data structure for viewing, manipulating and

5 reconstructing the image tiles; and

transferring the scanned, digital image tiles with the dynamic, self-executing program to allow viewing of a digital image of substantially larger image area than the area of the individually acquired tiles and at
10 multiple resolutions.

45. The method of Claim 44 further comprising the steps of:

displaying a first image comprising a portion of the specimen as an overall macro view; and

15 displaying a second image comprising higher resolution view from the specimen on the microscope slide at a higher magnification than the magnification of the overall macro view.

46. The method of Claim 45 further comprising:

20 selecting a point on said overall macro image with a marker; and

producing a corresponding higher magnification image at the location of the marker.

47. The method of Claim 44 further comprising

25 displaying the X-Y coordinates of said point.

48. The method of Claim 44 wherein said image tiles are stored as bit-mapped files.

49. The method of Claim 48 further comprising converting said bit-mapped files to JPEG files.

-57-

50. The method of Claim 44, comprising scanning and storing said images of said specimen at at least three magnifications.

51. A method in accordance with Claim 44
5 including the step of transferring the digital images to a web browser.

52. A method in accordance with Claim 51 including the step of transferring of the digital images over a dynamic Internet.

10 53. A method in accordance with Claim 51 including the step of transferring the digital images over a dynamic intranet.

54. A method in accordance with Claim 51 including the step of retoggling between lower
15 magnification images and higher magnification images stored on the web browser.

55. A method in accordance with Claim 46 wherein the step of selecting a point includes:
moving across tile boundaries to a desired point
20 on a selected macro tile image; and
executing a command to product the micro image from the selected macro tile image point.

56. A method in accordance with Claim 44 including the step of:
25 scrolling a portion of an image being viewed in a direction to cause the image being viewed to shift to include, in a new image, a portion of the image from a neighboring tiled image that was not previously viewed in the last image viewed by a user.

-58-

57. A program for creating a data structure of an image of a specimen on a microscope slide comprising:
a scanning routine for digitally scanning the image of the specimen on a microscope slide at a
5 plurality of image magnifications;
a recording routine for recording the scanned digital image in a series of contiguous image tiles; and
a linking routine for linking the series of contiguous image tiles with a dynamic, self-executing
10 program effective for viewing, manipulating and reconstructing the image tiles.

58. The program of Claim 57 further comprising a first display routine for displaying a micro image comprising a portion of the scanned image at a first
15 magnification and a second display routine for displaying a macro second image comprising an overall view from the specimen on the microscope slide.

59. The program of Claim 57 further comprising a routine for selecting a point on said macro image and
20 for producing a corresponding micro image at said point.

60. The program of Claim 57 further comprising a coordinate display routine for displaying the coordinates of said point to the user.

61. An apparatus for creating a data structure
25 comprising:

a computer-controlled microscope imaging system for digitally scanning images from a specimen on a microscope support at a plurality of image magnifications;
30 a program for recording the scanned digital images in a series of contiguous image tiles; and
a program for linking the series of contiguous image tiles with a dynamic, self-executing program

-59-

effective for viewing, manipulating and reconstructing the image tiles.

62. An apparatus is accordance with Claim 61 wherein a data compressor compresses the data of the
5 digitally scanned significantly to allow the scanned digitized images to be sent over the Internet.

63. An apparatus in accordance with Claim 61 wherein an addressable coordinate system provides addresses so that images can be seamed together and
10 higher magnification images can be easily located with respect to the lower magnification images.

64. An apparatus in accordance with Claim 61 wherein a program for scrolling allows the user to scroll a portion of a neighboring image into view.


15 65. An apparatus in accordance with Claim 61 including an address display to display the coordinates to assist multiple viewers to identify the same area for analysis and commentary.

66. An apparatus in accordance with Claim 61
20 further comprising:

a browser for storing the dynamic, self-executing program; and

a monitor for viewing the images stored on the monitor and for flipping back and forth between low
25 resolution macro images and high resolution micro images.

67. An apparatus in accordance with Claim 66 including a marker program to mark an addressable area on the macro image and to cause the addressed area to appear at a higher resolution, micro image on the monitor.



2/18

Fig. 1a







Fig. 1b



3/18

Fig. 2*Fig. 3*

4/18

Fig. 4



5/18

Fig. 5





Fig. 6



7/18

Fig. 7a

Uncompressed Data Files in BMP format

Contents of 'Dcis_027'

FinalScan.ini	Da29.bmp	Da55.bmp	Da81.bmp	Ss18.bmp
SlideScan.ini	Da3.bmp	Da56.bmp	Da82.bmp	Ss19.bmp
Da0.bmp	Da30.bmp	Da57.bmp	Da83.bmp	Ss2.bmp
Da1.bmp	Da31.bmp	Da58.bmp	Da84.bmp	Ss20.bmp
Da10.bmp	Da32.bmp	Da59.bmp	Da85.bmp	Ss21.bmp
Da100.bmp	Da33.bmp	Da6.bmp	Da86.bmp	Ss22.bmp
Da101.bmp	Da34.bmp	Da60.bmp	Da87.bmp	Ss23.bmp
Da102.bmp	Da35.bmp	Da61.bmp	Da88.bmp	Ss24.bmp
Da103.bmp	Da36.bmp	Da62.bmp	Da89.bmp	Ss25.bmp
Da104.bmp	Da37.bmp	Da63.bmp	Da9.bmp	Ss26.bmp
Da11.bmp	Da38.bmp	Da64.bmp	Da90.bmp	Ss27.bmp
Da12.bmp	Da39.bmp	Da65.bmp	Da91.bmp	Ss28.bmp
Da13.bmp	Da4.bmp	Da66.bmp	Da92.bmp	Ss29.bmp
Da14.bmp	Da40.bmp	Da67.bmp	Da93.bmp	Ss3.bmp
Da15.bmp	Da41.bmp	Da68.bmp	Da94.bmp	Ss30.bmp
Da16.bmp	Da42.bmp	Da69.bmp	Da95.bmp	Ss31.bmp
Da17.bmp	Da43.bmp	Da7.bmp	Da96.bmp	Ss32.bmp
Da18.bmp	Da44.bmp	Da70.bmp	Da97.bmp	Ss33.bmp
Da19.bmp	Da45.bmp	Da71.bmp	Da98.bmp	Ss34.bmp
Da2.bmp	Da46.bmp	Da72.bmp	Da99.bmp	Ss35.bmp
Da20.bmp	Da47.bmp	Da73.bmp	Ss1.bmp	Ss36.bmp
Da21.bmp	Da48.bmp	Da74.bmp	Ss10.bmp	Ss37.bmp
Da22.bmp	Da49.bmp	Da75.bmp	Ss11.bmp	Ss4.bmp
Da23.bmp	Da5.bmp	Da76.bmp	Ss12.bmp	Ss5.bmp
Da24.bmp	Da50.bmp	Da77.bmp	Ss13.bmp	Ss6.bmp
Da25.bmp	Da51.bmp	Da78.bmp	Ss14.bmp	Ss7.bmp
Da26.bmp	Da52.bmp	Da79.bmp	Ss15.bmp	Ss8.bmp
Da27.bmp	Da53.bmp	Da8.bmp	Ss16.bmp	Ss9.bmp
Da28.bmp	Da54.bmp	Da80.bmp	Ss17.bmp	mda027.TRA

Fig. 7b

BliFinalScanFrame.class
 BliMessageBox.class
 BliWebSlide.class


8/18


Fig. 8

Index.HTML for file 'Dcis_027'


Contents of 'Dcis_027'

WebSlide	Da29.jpg	Da55.jpg	Da81.jpg	Ss18.jpg
index.html	Da3.jpg	Da56.jpg	Da82.jpg	Ss19.jpg
Da0.jpg	Da30.jpg	Da57.jpg	Da83.jpg	Ss2.jpg
Da1.jpg	Da31.jpg	Da58.jpg	Da84.jpg	Ss20.jpg
Da10.jpg	Da32.jpg	Da59.jpg	Da85.jpg	Ss21.jpg
Da100.jpg	Da33.jpg	Da6.jpg	Da86.jpg	Ss22.jpg
Da101.jpg	Da34.jpg	Da60.jpg	Da87.jpg	Ss23.jpg
Da102.jpg	Da35.jpg	Da61.jpg	Da88.jpg	Ss24.jpg
Da103.jpg	Da36.jpg	Da62.jpg	Da89.jpg	Ss25.jpg
Da104.jpg	Da37.jpg	Da63.jpg	Da9.jpg	Ss26.jpg
Da11.jpg	Da38.jpg	Da64.jpg	Da90.jpg	Ss27.jpg
Da12.jpg	Da39.jpg	Da65.jpg	Da91.jpg	Ss28.jpg
Da13.jpg	Da4.jpg	Da66.jpg	Da92.jpg	Ss29.jpg
Da14.jpg	Da40.jpg	Da67.jpg	Da93.jpg	Ss3.jpg
Da15.jpg	Da41.jpg	Da68.jpg	Da94.jpg	Ss30.jpg
Da16.jpg	Da42.jpg	Da69.jpg	Da95.jpg	Ss31.jpg
Da17.jpg	Da43.jpg	Da7.jpg	Da96.jpg	Ss32.jpg
Da18.jpg	Da44.jpg	Da70.jpg	Da97.jpg	Ss33.jpg
Da19.jpg	Da45.jpg	Da71.jpg	Da98.jpg	Ss34.jpg
Da2.jpg	Da46.jpg	Da72.jpg	Da99.jpg	Ss35.jpg
Da20.jpg	Da47.jpg	Da73.jpg	Ss1.jpg	Ss36.jpg
Da21.jpg	Da48.jpg	Da74.jpg	Ss10.jpg	Ss37.jpg
Da22.jpg	Da49.jpg	Da75.jpg	Ss11.jpg	Ss4.jpg
Da23.jpg	Da5.jpg	Da76.jpg	Ss12.jpg	Ss5.jpg
Da24.jpg	Da50.jpg	Da77.jpg	Ss13.jpg	Ss6.jpg
Da25.jpg	Da51.jpg	Da78.jpg	Ss14.jpg	Ss7.jpg
Da26.jpg	Da52.jpg	Da79.jpg	Ss15.jpg	Ss8.jpg
Da27.jpg	Da53.jpg	Da8.jpg	Ss16.jpg	Ss9.jpg
Da28.jpg	Da54.jpg	Da80.jpg	Ss17.jpg	






12/18

Fig. 11

13/18

Fig. 12

14/18

Fig. 13

Microscope Objective Properties

Position 1 Position 2 Position 3 Position 4 Position 5 Position 6 Position 7

☒ Color
☐ Grayscale

Filter Turret
☒ 680nm Filter
☐ 580nm Filter
☐ Open
☐ Open
☐ Open

Magnification 125

Condenser Diaphragm
100%
0 240 255

Stage Properties
X EditXStepsP steps per field width
Y EditYStepsP steps per field height

Magnification Change Offsets
X EditXOffset stage offset
Y EditYOffset stage offset
Z EditZOffset focus offset

Lamp Voltage
10.5v
0 64 255

Reflected Light
☐ Reflected Light

Transmitted Light
☒ Transmitted Light



Field Diaphragm
100%
0 240 255

N.D. Wheel 2
☒ 100%
☐ 6%
☐ D4%
☐ D%

N.D. Wheel 1
☒ 12%
☐ 25%
☐ 50%
☐ 100%

OK Cancel

15/18

Fig. 14*Fig. 15*

16/18

Fig. 16








Fig. 16A



17/18

Fig. 17*Fig. 17A*



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/04011

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :G06K 9/00

US CL :382/133

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 382/128, 133, 134, 284, 294, 318, 319; 128/922

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,257,182 A (LUCK et al) 26 October 1993, Figures 1 & 2; column 3, line 23 through column 5, line 12; column 7, line 1 through column 8, line 5.	1-67
Y	US 5,287,272 A (RUTENBERG et al) 15 February 1994, Figure 3A; column 4, lines 39-62; column 12, lines 19-56; column 13 lines 27-61.	1-67
A	US 5,544,650 A (BOON et al) 13 August 1996, Figure 2; column 4, lines 32-65.	1-67
A	US 5,428,690 A (BACUS et al) 27 June 1995, column 3, lines 12-38.	1-67
A	US 5,252,487 A (BACUS et al) 12 October 1993, see the entire document.	1-67

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
Q document referring to an oral disclosure, etc. exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

15 JUNE 1998

Date of mailing of the international search report

14 AUG 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ANDREW W. JOHNS

Telephone No. (703) 305-3900